



END CAP


HEAT TRACE CABLE

TO POWER SUPPLY AT DISCONNECT SWITCH


WATER TIGHT CONTROL BOX

SET ON AT 35°F

HEAT TRACE CONTROL BOX DIAGRAM
NO SCALE



INSTALLATION DETAIL NO SCALE



INSTALLATION AT VALVES
NO SCALE

<u>DRAWING NOTES:</u> 1 PROVIDE WEATHER RESISTANT LABELING ON EXTERIOR OF JACKET IDENTIFYING PIPES AS BEING "ELECTRIC TRACED" WITH VOLTAGE INDICATED.

NOTE:

THIS DRAWING IS PROVIDED FOR INSTRUCTIONAL DESIGN PURPOSES ONLY BASED ON METROLINX GO TRANSIT DESIGN GUIDELINES AND REQUIREMENTS. THE CONSULTANT SHALL VERIFY FOR LOCAL CODE COMPLIANCE, EXISTING SITE CONDITIONS AND INTER DISCIPLINARY DRAWING COORDINATION. ALL DIMENSIONS AND SPECIFICATIONS SHOULD BE VERIFIED BY CONSULTANT AND/OR CONTRACTOR BEFORE ACTUAL CONSTRUCTION BEGINS.

NOTE: — ALL DIMENSIONS SHOWN ARE IN METERS AND/OR MILLIMETERS UNLESS OTHERWISE NOTED.

(— THIS DÉTAIL IS ONLY APPLICABLE TO METAL/STÉEL PIPING)

(2)

 Drawn:
 Checked:

 Dessin:
 I.K.

 Checked:
 Verification:

 K.W.

Scale:

Echelle:

N.T.S

Date: 2022/11/25

PIPE HEAT TRACING DETAILS

△ METROLINX

Drawing Number Dessin Numero