



**TURNOUT DATA:**  
 FROG NO -----8  
 LENGTH OF SW.P.T.-----5029(16'-6")  
 HEEL SPREAD-----159(6 1/4")  
 LEAD-----20695(67'-10 3/4")  
 PS TO H.F.-----23133(75'-10 3/4")  
 14143(46'-4 3/4") STRAIGHT CLOSURE LENGTH

- NOTES**
- TURNOUT TO BE INSTALLED AND MAINTAINED IN ACCORDING WITH THE LATEST ISSUE OF:  
 RM .3500 TURNOUTS  
 RM .3502 POWER, SPRING AND INSTALLED SWITCH  
 RM .3506 SWITCH STAND, SWITCH LAMPS AND TARGETS, WHERE APPLICABLE
  - WHEN REFERRING TO MANUAL TURNOUTS, DRAWING NUMBER MUST BE STATED AS A OR B:  
 A-RIGHT HAND TURNOUT  
 B-LEFT HAND TURNOUT
  - FOR GENERAL ARRANGEMENT OF SWITCH STAND & COMBINATION SEE GTS-701 AND GTS-702
  - FOR THE VARIOUS STANDARD TURNOUT COMBINATIONS SEE INDEX SHEET GTS-0
  - TURNOUT GEOMETRY, FOR TABLES OF DIMENSIONS AND OFFSETS SEE GTS-1

**METRIC CONVERSION: 1 inch=25.4mm, 1 foot=304.8mm**

No.	Date	Revision	By	Approved
1	18/07/27	ADDED IMPERIAL TO METRIC CONVERSION NOTE		

Standard / **NO. 8 TURNOUT-16'6" POINTS INSULATED R.B.M FROG 132LB. R.E. RAIL**

Drawn MG Checked GGS Approved *[Signature]*  
 Vp Engineering & Asset Management

**METROLINX**

Date DEC 15, 2017 Plan Number GTS-0063 Rev 1  
 REFERENCE: TS-63 A/B Sheet 1 OF 1

