



NOTES

1. WHEN REFERRING TO SWITCH PLATES, PLAN AND PLATE NUMBERS MUST BE STATED TO INDICATE SPECIFIC PLATE REQUIRED.
2. IDENTIFICATION CHARACTERS (1/2" MINIMUM HEIGHT) TO BE STAMPED ON EACH PLATE AS SHOWN.
3. ALL DIMENSIONS ARE IN INCHES.
4. UNLESS OTHERWISE SPECIFIED ALL TOLERANCES TO BE ± 1/32.

MATERIAL

PLATES TO CONFORM TO THE LATEST REVISION OF GO TRANSIT TRACK STANDARDS OR IN GENERAL WITH LATEST REVISION OF A.S.T.M. SPECIFICATION FOR COMMERCIAL QUALITY HOT ROLLED BAR STEEL A-675 CHEMICAL REQUIREMENT.

	MINIMUM	MAXIMUM
CARBON	0.15 %	0.25 %
MANGANESE	0.30 %	0.60 %
PHOSPHORUS		0.04 %
SULPHUR		0.05 %

PLATES	A ±1/8	B ±1/16	C	D	E	WEIGHT (LBS)	STOCK NUMBERS	
							NEW	PART WORN
SP-668	29-1/4	27-7/8	23-9/16	16-57/64	1°			
SP-669	30	28-5/8	24-5/64	17-13/32	1°			
SP-670	30-1/2	29-1/8	24-39/64	17-15/16	1°			
SP-671	31	29-5/8	25-5/32	18-15/32	1°			
SP-672	31-1/2	30-1/8	25-23/32	19-1/32	1°			

0	17/12/15	REVISED PDF VERSION ESTABLISHED	
No.	Date	Revision	By Approved

Standard / **FOR EQUILATERAL TURNOUT SWITCH PLATES**

Drawn MG Checked RP Approved *RP*
VP Corridor Infrastructure



METROLINX

Date DEC 15, 2017 Plan Number GTS-0642 Rev 0

REFERENCE: TS-642

Sheet 1 OF 1