

TYPICAL PANDROL SHOULDER INSTALLATION

NOTES



1. WHEN REFERRING TO SWITCH PLATES, PLAN AND PLATE NUMBERS MUST BE STATED TO INDICATE SPECIFIC PLATE REQUIRED.
2. IDENTIFICATION CHARACTERS (1/2 "MINIMUM HEIGHT) TO BE STAMPED ON EACH PLATE AS SHOWN.
3. ALL DIMENSIONS ARE IN INCHES.
4. UNLESS OTHERWISE SPECIFIED ALL TOLERANCES TO BE $\pm 1/32$.

MATERIAL

PLATES TO CONFORM TO THE LATEST REVISION OF GO TRANSIT TRACK STANDARDS OR IN GENERAL WITH LATEST REVISION OF A.S.T.M. SPECIFICATION FOR COMMERCIAL QUALITY HOT ROLLED BAR STEEL A-675 CHEMICAL REQUIREMENT.

	MINIMUM	MAXIMUM
CARBON	0.15 %	0.25 %
MANGANESE	0.30 %	0.60 %
PHOSPHORUS		0.04 %
SULPHUR		0.05 %

PLATES	A $\pm 1/8$	B $\pm 1/16$	C	D	E	WEIGHT (LBS.)	STOCK NUMBERS	
							NEW	PART WORN
SP-673	32-1/4	30-7/8	26-9/32	19-5/8	1°			
SP-674	32-3/4	31-3/8	26-55/64	20-13/64	1°			
SP-675	33-1/4	31-7/8	27-7/16	20-25/32	1°			

0	17/12/15	REVISED PDF VERSION ESTABLISHED
No.	Date	Revision
		By Approved
Standard / FOR EQUILATERAL TURNOUT SWITCH PLATES		
Drawn	MG	Checked RP
		Approved <i>RP</i> VP Corridor Infrastructure
 		
Date	DEC 15, 2017	Plan Number GTS-0643 Rev 0
REFERENCE: TS-643		Sheet 1 OF 1