



METRIC CONVERSION: 1 inch=25.4mm, 1 foot=304.8mm

0	18/08/31	REVISED PDF VERSION ESTABLISHED	
No.	Date	Revision	By Approved
Standard/		FENCING AND GATES RIGHT OF WAY	
Drawn	MG	Checked	GGG
Approved		VP Engineering & Asset Management	

REMARKS: 1. FOR SPECIFICATION OF WOVEN WIRE FENCE MATERIAL SEE 13-1 FOR SPECIFICATION OF WOVEN WIRE FENCE GATES SEE 13-3 (THIS PLAN FORMS PART OF THESE SPECIFICATIONS)
2. FOR SPECIFICATION OF WOOD FENCE POST SEE 54W-5.1
3. FENCING & GATES TO BE INSTALLED AND MAINTAINED IN ACCORDANCE WITH RM RIGHT OF WAY FENCING & GATES. (THIS PLAN FORMS PART OF THIS CIRCULAR.)

DETAIL OF 3/4" HINGE BOLTS

DETAIL OF WIRE SPLICE

ANCHORING- END, CORNER AND GATE POSTS SHALL BE ANCHORED AS SHOWN EXCEPT IN ROCK AREA. TWO 91.4mm(3") LONG CEDAR CLEATS MADE FROM FENCE POSTS SPLIT IN HALF TO BE USED. CLEATS TO BE NOTCHED INTO POST AND SECURELY SPIKED BY AT LEAST TWO COATED SPIRAL NAILS.

DOUBLE GATE CHAIN TO SUIT GATES

STOP DETAIL

DOUBLE GATE CHAIN TO SUIT GATES

WHERE APPROVED BY TRACK & ROADWAY ENGINEER

THE HORIZONTAL WIRES SHALL BE SPACED AND STRETCHED UNIFORMLY AND PARALLEL. ANY SMALL UNDULATIONS OF THE GROUND SHALL BE LEVELLED SO THAT BOTTOM WIRE OF FENCE IS UNIFORM DISTANCE FROM GROUND AND STRAIGHT BETWEEN POSTS. STAY WIRES SHALL BE STRAIGHT AND VERTICAL AND UNIFORMLY SPACED.

POSTS IN GROUND DEPRESSIONS SHALL BE ANCHORED AS SHOWN

DEPRESSIONS-HILLS-HOLLOES SPECIAL CARE SHOULD BE TAKEN WHEN SETTINGS POSTS IN SLIGHT HOLLOW AND STEEP GRADES.

Date AUG 31/2018 Plan Number GTS-2211 Rev 0

REFERENCE: TS-2211 Sheet 1 OF 1